

BALL VALVES

Brass Threaded Ball Valve



TECHNICAL DATA

Connection	DIN2999 BSPP
Working pressure	PN16 / PN25 / PN40
Working temperature	-10°C / +120°C

WHERE IT IS USED

- Water - Wastewater
- Heating - Cooling Systems
- Maritime Applications

DIMENSION TABLE

DN	NPS	L	L1	H	KG
15	1/2"	54	80	37	0,15
20	3/4"	61	95	53	0,25
25	1"	73	115	55	0,45
32	1 1/4"	83	115	59	0,65
40	1 1/2"	95	125	77	0,95
50	2"	113	145	90	1,45
65	2 1/2"	132	230	107	3,65
80	3"	149	250	120	5,60
100	4"	174	250	135	9,10

MATERIAL LIST

No	Part	Material
1	BODY	MS58
2	CAP	MS58
3	BALL	MS58
4	GASKET	PTFE
5	STEM	MS58
6	O-RING	EPDM / VITON
7	NUT	STEEL

No	Part	Material
8	HANDLE	STEEL

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 26 (PDF 29)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

METROEND MÜHENDİSLİK SAN. TİC. LTD. ŞTİ

Küçükbakkalköy Mah. Selvili Sk. No: 4, İç Kapı No: 20,

Ataşehir / İstanbul

+90 546 224 41 94 · sales@metroend.com

<https://vana.bogahost.com/en/products/valves/ball-valves/brass-threaded-ball-valve>

www.metroend.com