

GATE VALVES

Brass Threaded Gate Valve



TECHNICAL DATA

Connection	DIN2999
Working pressure	PN16
Working temperature	-10°C / +120°C

WHERE IT IS USED

- Chemical - Petrochemical
- Water - Wastewater
- Heating - Cooling Systems
- Maritime Applications
- Mining Applications
- Power Stations

DIMENSION TABLE

DN	NPS	L	D	H	d	A	KG
15	1/2"	48	60	70	13	15,5	0,20
20	3/4"	51	60	75	19	16,5	0,30
25	1"	58	70	88	25	19	0,45
32	1 1/4"	68	70	112	32	21,5	0,65
40	1 1/2"	70	70	120	38	21,5	0,90
50	2"	82	80	140	50	26	1,40
65	2 1/2"	75	100	172	63	20	2,80
80	3"	85	100	200	77	22,5	4,20
100	4"	102	132	240	100	26,5	8,00

MATERIAL LIST

No	Part	Material
1	BODY	BRASS
2	BONNET	BRASS

No	Part	Material
3	WEDGE	BRASS
4	GASKET	FIBER
5	STEM	BRASS
6	O-RING	EPDM / VITON
7	HANDWHEEL	STEEL
8	SCREW	STEEL

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 42 (PDF 45)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

METROEND MÜHENDİSLİK SAN. TİC. LTD. ŞTİ

Küçükbakkalköy Mah. Selvili Sk. No: 4, İç Kapı No: 20,
Ataşehir / İstanbul

+90 546 224 41 94 · sales@metroend.com

<https://vana.bogahost.com/en/products/valves/gate-valves/brass-threaded-gate-valve>
www.metroend.com