

SOLENOID VALVES

Brass Threaded General Purpose Solenoid Valve



TECHNICAL DATA

Connection	DIN 2999
Working pressure	PN16
Working temperature	-10°C / +80°C

WHERE IT IS USED

- Power Plants
- Chemical - Petrochemical
- Maritime Applications
- Heating - Cooling Systems
- Food
- Mining Applications
- Water - Wastewater

DIMENSION TABLE

DN	NPS	A	B	C	D	E	F	G	KG
6	1/8"	105,3	69	76,5	26,8	26,9	44	13,4	0,67
8	1/4"	105,3	69	76,5	26,8	26,9	44	13,4	0,68
10	3/8"	105,3	69	76,5	26,8	26,9	44	13,4	0,62
15	1/2"	105,3	69	76,5	26,8	26,9	44	13,4	0,60
20	3/4"	109,8	80	86,8	31,8	31,9	53,8	15,3	0,75
25	1"	120,3	89	95,5	40,9	40,7	62	20,5	1
32	1 1/4"	110	117	130	48	74	24		2,95
40	1 1/2"	140	127	140	56	98	28		2,85
50	2"	145	143	156	70	110	35		3,3

MATERIAL LIST

No	Part	Material
1	BODY	BRASS

No	Part	Material
2	PLUNGER SEAL	NBR
3	ENCLOSING TUBE	AISI430 / AISI304
4	PLUNGER	AISI430
5	SPRING	AISI302
6	SHADING RING	COPPER
7	SEAT	BRASS
8	O-RING	NBR
9	DIAPHRAM SEAT	SEAL NBR
10	COVER SCREWS	ST . STEEL
11	COVER	BRASS

PENDING REVIEW

At least one data plate field of this product could not be read from the source catalog and was left blank. Blank fields have not been estimated. Please confirm the values with the company before a binding offer.

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 79 (PDF 82)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

METROEND
MÜHENDİSLİK SAN.
TİC. LTD. ŞTİ

Küçükbakkalköy Mah.
Selvili Sk. No: 4, İç
Kapı No: 20, Ataşehir
/ İstanbul
+90 546 224 41
94 ·
sales@metroend.com

<https://vana.bogahost.com/en/products/valves/solenoid-valves/brass-threaded-general-purpose-solenoid-valve>
www.metroend.com