

CHECK VALVES

Brass Threaded Spring Loaded Vertical Check Valve



TECHNICAL DATA

Connection	DIN2999
Working pressure	PN16
Working temperature	-10°C / +90°C

WHERE IT IS USED

▪ Chemical - Petrochemical	▪ Maritime Applications
▪ Water - Wastewater	▪ Mining Applications
▪ Heating - Cooling Systems	▪ Power Stations

DIMENSION TABLE

kolon_1	DIN2999	kolon_3	kolon_4	PN16
1	GÖVDE	BODY	MS58	
2	KAPAK	BONNET	MS58	
3	KLAPE	DISC		POLYMER PLASTIC
4	CONTA	GASKET	NBR	
5	YAY	SPRING	AISI302	

MATERIAL LIST

No	Part	Material
1	BODY	MS58
2	BONNET	MS58
3	DISC	POLYMER PLASTIC
4	GASKET	NBR
5	SPRING	AISI302

PENDING REVIEW

At least one data plate field of this product could not be read from the source catalog and was left blank. Blank fields have not been estimated. Please confirm the values with the company before a binding offer.

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 66 (PDF 69)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

METROEND
MÜHENDİSLİK SAN.
TİC. LTD. ŞTİ

Küçükbakkalköy Mah.
Selvili Sk. No: 4, İç
Kapı No: 20, Ataşehir
/ İstanbul
+90 546 224 41
94 ·
sales@metroend.com

<https://vana.bogahost.com/en/products/valves/check-valves/brass-threaded-spring-loaded-vertical-check-valve>
www.metroend.com