

BALL VALVES

Bronze Threaded Ball Valve



TECHNICAL DATA

Connection	DIN2999 BSPT
Working pressure	PN25
Working temperature	-20°C / +170°C

WHERE IT IS USED

- Water - Wastewater
- Heating - Cooling Systems
- Maritime Applications

DIMENSION TABLE

DN	NPS	L	L1	H	KG
15	1/2"	53	95	44	0,230
20	3/4"	61	110	51	0,37
25	1"	71	110	55	0,54
32	1 1/4"	85	140	65	0,84
40	1 1/2"	92	140	70	1,13
50	2"	114	160	83	1,88

MATERIAL LIST

No	Part	Material
1	BODY	RG5
2	CAP	RG5
3	BALL	PİRİNÇ / BRASS
4	BALL SEAT	PTFE
5	STEM	PİRİNÇ / BRASS
6	WASHER	PTFE
7	GLAND NUT	PİRİNÇ / BRASS
8	HANDLE	AISI 304
9	HANDLE SLEEVE	PVC
10	HANDLE NUT	STEEL

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 25 (PDF 28)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

METROEND MÜHENDİSLİK SAN. TİC. LTD. ŞTİ

Küçükbakkalköy Mah. Selvili Sk. No: 4, İç Kapı No:

20, Ataşehir / İstanbul

+90 546 224 41 94 · sales@metroend.com

<https://vana.bogahost.com/en/products/valves/ball-valves/bronze-threaded-ball-valve>

www.metroend.com