

GATE VALVES

Bronze Threaded Gate Valve



TECHNICAL DATA

Connection	DIN2999
Working pressure	PN20
Working temperature	-20°C / +170°C

WHERE IT IS USED

- Water - Wastewater
- Heating - Cooling Systems
- Maritime Applications

DIMENSION TABLE

kolon_1	kolon_2	kolon_3	kolon_4	CAST IRON
4	MİL		STEM	CW602N
5		SALMASTRA SOMUNU	PACKING NUT	CW617N
6	RİNG		RING	CW617N
7	SALMASTRA		PACKING	PTFE
8	MİL BURCU		STEM BUSH	CW602N
9	KAPAK		BONNET	CC491K
10	CONTA		GASKET	PTFE
11	DİSK		DISC	CC491K
12	GÖVDE		BODY	CC491K

MATERIAL LIST

No	Part	Material
1	NUT	CW617N
2	I.D PLATE	ALUMINIUM
3	HANDWHEEL	ALUMINIUM CAST IRON

No	Part	Material
4	STEM	CW602N
5	PACKING NUT	CW617N
6	RING	CW617N
7	PACKING	PTFE
8	STEM BUSH	CW602N
9	BONNET	CC491K
10	GASKET	PTFE
11	DISC	CC491K
12	BODY	CC491K

PENDING REVIEW

At least one data plate field of this product could not be read from the source catalog and was left blank. Blank fields have not been estimated. Please confirm the values with the company before a binding offer.

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 43 (PDF 46)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

METROEND MÜHENDİSLİK SAN. TİC. LTD. ŞTİ

Küçükbakkalköy Mah. Selvili Sk. No: 4, İç Kapı No:
20, Ataşehir / İstanbul
+90 546 224 41 94 · sales@metroend.com

<https://vana.bogahost.com/en/products/valves/gate-valves/bronze-threaded-gate-valve>
www.metroend.com