

GLOBE VALVES

Bronze Threaded Globe Valve



TECHNICAL DATA

Connection	ISO228
Working pressure	PN20
Working temperature	-20°C / +170°C

WHERE IT IS USED

- Chemical - Petrochemical
- Water - Wastewater
- Heating - Cooling Systems
- Maritime Applications
- Mining Applications
- Power Stations

DIMENSION TABLE

kolon_1	ISO228	kolon_3	kolon_4	PN20
1		HENDİL SOMUNU	HANDWHEEL NUT	ST.STEEL
2	ETİKET		I.D PLATE	ALUMINIUM
3	HENDİL		HANDWHEEL	ALUMINIUM
4	MİL		STEM	CW602N
5		SALMASTRA SOMUNU	PACKING NUT	CW614N
6	SALMASTRA		PACKING	PTFE
7	KAPAK		BONNET	CC491K
8	DİSK		DISC	CC491K
9	GÖVDE		BODY	CC491K

MATERIAL LIST

No	Part	Material
1	HANDWHEEL NUT	ST.STEEL
2	I.D PLATE	ALUMINIUM

No	Part	Material
3	HANDWHEEL	ALUMINIUM
4	STEM	CW602N
5	PACKING NUT	CW614N
6	PACKING	PTFE
7	BONNET	CC491K
8	DISC	CC491K
9	BODY	CC491K

PENDING REVIEW

At least one data plate field of this product could not be read from the source catalog and was left blank. Blank fields have not been estimated. Please confirm the values with the company before a binding offer.

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 13 (PDF 16)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

METROEND MÜHENDİSLİK SAN. TİC. LTD. ŞTİ

Küçükbakkalköy Mah. Selvili Sk. No: 4, İç Kapı
No: 20, Ataşehir / İstanbul
+90 546 224 41 94 · sales@metroend.com

<https://vana.bogahost.com/en/products/valves/globe-valves/bronze-threaded-globe-valve>
www.metroend.com