

CHECK VALVES

Bronze Threaded Spring Loaded Vertical Check Valve



TECHNICAL DATA

Connection	ISO228
Working pressure	PN20
Working temperature	-20°C / +170°C

WHERE IT IS USED

Chemical - Petrochemical	Maritime Applications
Water - Wastewater	Mining Applications
Heating - Cooling Systems	Power Stations

DIMENSION TABLE

kolon_1	ISO228	kolon_3	PN20
1	GÖVDE	BODY	RG5
2	DİSK	DISC	RG5
3	SİT	SEAT	NBR
4	YAY	SPRING	AISI304
5	CONTA	GASKET	PTFE
6	KAPAK	BONNET	RG5

MATERIAL LIST

No	Part	Material
1	BODY	RG5
2	DISC	RG5
3	SEAT	NBR
4	SPRING	AISI304
5	GASKET	PTFE

No	Part	Material
6	BONNET	RG5

PENDING REVIEW

At least one data plate field of this product could not be read from the source catalog and was left blank. Blank fields have not been estimated. Please confirm the values with the company before a binding offer.

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 68 (PDF 71)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

METROEND
MÜHENDİSLİK SAN.
TİC. LTD. ŞTİ

Küçükbakkalköy Mah.

Selvili Sk. No: 4, İç

Kapı No: 20, Ataşehir

/ İstanbul

+90 546 224 41

94 ·

sales@metroend.com

<https://vana.bogahost.com/en/products/valves/check-valves/bronze-threaded-spring-loaded-vertical-check-valve>

www.metroend.com