

BALANCING VALVES

Bronze Threaded Static Balancing Valve



TECHNICAL DATA

Connection	ISO7
Working pressure	PN25
Working temperature	-10°C / +120°C

WHERE IT IS USED

- Power Plants
- Chemical - Petrochemical
- Maritime Applications
- Heating - Cooling Systems
- Food
- Mining Applications
- Water - Wastewater

DIMENSION TABLE

kolon_1	ISO7	kolon_3	kolon_4	kolon_5	kolon_6	PN25
1	GÖVDE		BODY			RG5
2	KAPAK		BONNET			BRASS
3	HENDİL			HANDWHEEL		EBONITE
4	MİL		MİL			BRASS
5	DİSK		DISC			BRASS
6		ÖLÇÜM PROBU			MEASUREMENT PROBE	BRASS

MATERIAL LIST

No	Part	Material
1	BODY RG5	
2	BONNET BRASS	
3	HANDWHEEL EBONITE	
4	MİL BRASS	

No	Part	Material
5	DISC BRASS	
6	MEASUREMENT PROBE BRASS	

PENDING REVIEW

At least one data plate field of this product could not be read from the source catalog and was left blank. Blank fields have not been estimated. Please confirm the values with the company before a binding offer.

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 77 (PDF 80)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

**METROEND MÜHENDİSLİK
SAN. TİC. LTD. ŞTİ**

Küçükbakkalköy Mah. Selvili
Sk. No: 4, İç Kapı No: 20,
Ataşehir / İstanbul
+90 546 224 41 94 ·
sales@metroend.com

<https://vana.bogahost.com/en/products/valves/balancing-valves/bronze-threaded-static-balancing-valve>
www.metroend.com