

CHECK VALVES

Bronze Threaded Swing Check Valve



TECHNICAL DATA

Connection	DIN2999
Working pressure	PN20
Working temperature	-20°C / +170°C

WHERE IT IS USED

- Chemical - Petrochemical
- Water - Wastewater
- Heating - Cooling Systems
- Maritime Applications
- Mining Applications
- Power Stations

DIMENSION TABLE

DN	NPS	L	H	d	KG
15	1/2"	58	37	12	0,20
20	3/4"	66	43	18	0,25
25	1"	76	49	24	0,36
32	1 1/4"	88	57,5	30,6	0,56
40	1 1/2"	96	63	37	0,90
50	2"	112	72	48,6	1,25

MATERIAL LIST

No	Part	Material
1	BODY	RG5
2	DISC	RG5 PİRİNÇ / BRASS 1
3	HINGE	RG5
4	HINGE PIN	ST.STEEL
5	PLUG	RG5
6	HINGE NUT	PİRİNÇ / BRASS

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 70 (PDF 73)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

**METROEND MÜHENDİSLİK SAN. TİC.
LTD. ŞTİ**

Küçükbakkalköy Mah. Selvili Sk. No: 4, İç
Kapı No: 20, Ataşehir / İstanbul
+90 546 224 41 94 ·
sales@metroend.com

<https://vana.bogahost.com/en/products/valves/check-valves/bronze-threaded-swing-check-valve>
www.metroend.com