

CHECK VALVES

Dual Plate Check Valve



TECHNICAL DATA

Connection	DIN1092-2
Working pressure	PN16 / PN40
Working temperature	-10°C / +100°C

WHERE IT IS USED

- Chemical - Petrochemical
- Water - Wastewater
- Heating - Cooling Systems
- Maritime Applications
- Mining Applications
- Power Stations

DIMENSION TABLE

DN	ØD	Ød	h	R	KG
50	107	65	43	28,8	1,50
65	127	80	46	36,1	2,40
80	142	94	64	43,4	3,60
100	162	117	64	50	5,70
125	192	145	70	68,2	7,30
150	218	170	76	78,6	9,00
200	268	224	89	104,5	17,00
250	327	265	114	128	26,00
300	384	310	114	148,3	42,00
350	438	360	127	172,4	55,00
400	488	410	140	198	75,00

MATERIAL LIST

No	Part	Material
1	BODY	GG25 / GGG40
2	DISC	AISI304 / AISI316 /
3	SEAT	NBR / EPDM
4	HINGING PIN	Gr 33
5	SPRING	AISI304
6	STEM	AISI416
7	WASHER	AISI304
8	DISC WASHER	AISI304
9	GASKET	NBR
10	GRUB SCREW	ST37

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 64 (PDF 67)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

METROEND MÜHENDİSLİK SAN. TİC. LTD. ŞTİ

Küçükbakkalköy Mah. Selvili Sk. No: 4, İç Kapı No: 20,

Ataşehir / İstanbul

+90 546 224 41 94 · sales@metroend.com

<https://vana.bogahost.com/en/products/valves/check-valves/dual-plate-check-valve>

www.metroend.com