

Flanged 2 Piece Ball Valve



Connection	DIN1092-2
Working pressure	PN16
Working temperature	• GG25 Cast Iron: -29°C / +150°C • GGG40.3 Ductile Iron: -29°C / +180°C • RG5 - RG10 Bronze Casting: -29°C / +110°C

▪ Chemical - Petrochemical	▪ Maritime Applications
▪ Water - Wastewater	▪ Mining Applications
▪ Heating - Cooling Systems	▪ Power Stations

[illegible]

MATERIAL LIST

No	Part	Material
1	BODY	GG25 / GGG40 / RG5 / RG10
2	BONNET	GG25 / GGG40 / RG5 / RG10
3	BALL	AISI420 / AISI304 / AISI316 / RG5
4	STEM	AISI420
5	BALL SEAL	PTFE
6	BODY SEAL	PTFE
7	NECK SEAL	PTFE
8	PRES.RING	ST42
9	WASHER	CK70
10	COUNTER NUT	5.6.
11	BOLT	ST42
12	NUT	5.6.
13	STOP. PIM	ST42
14	HANDLE	ST37

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 17 (PDF 20)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

METROEND MÜHENDİSLİK SAN. TİC. LTD. ŞTİ

Küçükbakkalköy Mah. Selvili Sk. No: 4, İç Kapı No:

20, Ataşehir / İstanbul

+90 546 224 41 94 · sales@metroend.com

<https://vana.bogahost.com/en/products/valves/ball-valves/flanged-2-piece-ball-valve>

www.metroend.com