

SIGHT GLASSES

Flanged Sight Glass



TECHNICAL DATA

Connection	EN 1092-2
Working pressure	PN16
Working temperature	-10°C / +180°C

WHERE IT IS USED

- Power Plants
- Chemical - Petrochemical
- Maritime Applications
- Heating - Cooling Systems
- Food
- Mining Applications
- Water - Wastewater

DIMENSION TABLE

DN	ØD	Øk	Øg	L	b	Ødxn	KG
15	95	65	46	130	14	14x1	2,80
20	105	75	56	150	16	14x4	3,50
25	115	85	65	160	16	14x4	4,30
32	140	100	76	180	18	18x4	6,70
40	150	110	84	200	18	18x4	7,20
50	165	125	99	230	20	18x4	11,50
65	185	145	118	290	20	18x4	17,80
80	200	160	132	310	22	18x8	21,00
100	220	180	156	350	24	18x8	31,20
125	250	210	184	400	26	18x8	39,00
150	285	240	211	480	26	22x8	55,80
200	340	295	266	600	30	22x12	89,00

DN	ØD	Øk	Øg	L	b	Ødxn	KG
250	405	355	319	730	32	26x12	98,00

MATERIAL LIST

No	Part	Material
1	BODY	GG25 / AISI304 / AISI316
2	COVER	GG25 / AISI304 / AISI316
3	GLASS	SEKURITE
4	BODY SEAL	PTFE
5	BOLT	5.6.

PENDING REVIEW

At least one data plate field of this product could not be read from the source catalog and was left blank. Blank fields have not been estimated. Please confirm the values with the company before a binding offer.

DATA SOURCE
Metroend-Urun-Katalogu.pdf · printed page 84 (PDF 87)
All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.