

CHECK VALVES

Flanged Swing Check Valve



TECHNICAL DATA

Connection	DIN1092-2
Working pressure	PN16
Working temperature	-10°C / +120°C

WHERE IT IS USED

- Chemical - Petrochemical
- Water - Wastewater
- Heating - Cooling Systems
- Maritime Applications
- Mining Applications
- Power Stations

DIMENSION TABLE

DN	ØD	Øk	Øg	L	b	H	Ødxn	KG
40	150	110	88	180	18	249	18x4	9
50	165	125	102	200	20	254	18x4	11
65	185	145	122	240	20	271	18x4	17
80	200	160	138	260	20	311	18x8	20
100	220	180	158	300	24	344	18x8	28
125	250	210	188	350	26	420	18x8	46
150	285	240	212	400	26	498	22x8	61
200	340	295	268	500	30	550	22x12	72
250	405	355	320	600	32	585	26x12	122

MATERIAL LIST

No	Part	Material
1	BODY	GG25 / GGG40
2	BONNET	GG25 / GGG40
3	DISC	GG25 / GGG40 +NBR
4	STEM	ST.STEEL

No	Part	Material
5	SEAT	BRASS / BRONZE
6	GASKET	EPDM / NBR

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 61 (PDF 64)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

METROEND MÜHENDİSLİK SAN. TİC. LTD. ŞTİ

Küçükbakkalköy Mah. Selvili Sk. No: 4, İç Kapı No:

20, Ataşehir / İstanbul

+90 546 224 41 94 · sales@metroend.com

<https://vana.bogahost.com/en/products/valves/check-valves/flanged-swing-check-valve>

www.metroend.com