

GATE VALVES

Gate Valve PN6 DIN3204



TECHNICAL DATA

Connection	DIN1092-2
Working pressure	PN16
Working temperature	-10°C / +120°C

WHERE IT IS USED

- Chemical - Petrochemical
- Water - Wastewater
- Heating - Cooling Systems
- Maritime Applications
- Mining Applications
- Power Stations

DIMENSION TABLE

DN	ØD	Øk	Øg	b	Ødxn	ØD1	H	L	KG
40	130	100	78	16	14x4	160	185	140	7
50	140	110	88	16	14x4	160	190	150	8
65	160	130	108	16	14x4	160	210	170	12
80	190	150	124	18	19x4	160	235	180	15
100	210	170	144	18	19x4	200	265	190	20
125	240	200	174	20	19x8	250	350	200	34
150	265	225	199	20	19x8	250	380	210	43

MATERIAL LIST

No	Part	Material
1	BODY	GG25 / GGG40 / RG5 /
2	SEAT	BRASS / BRONZE
3	WEDGE	GG25 / GGG40 / RG5 /
4	STEM	AISI420

No	Part	Material
5	GASKET	NBR / VITON
6	BONNET	GG25 / GGG40 / RG5 /
7	HANDWHEEL	GG25

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 39 (PDF 42)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

METROEND MÜHENDİSLİK SAN. TİC. LTD. ŞTİ

Küçükbakkalköy Mah. Selvili Sk. No: 4, İç Kapı No: 20,

Ataşehir / İstanbul

+90 546 224 41 94 · sales@metroend.com

<https://vana.bogahost.com/en/products/valves/gate-valves/gate-valve-pn6-din3204>

www.metroend.com