

OMEGA FLEXES

OMEGA V-FLEX BUTT WELD

MTE-2030



TECHNICAL DATA

Connection	Butt Weld - Kaynak Boyunlu
Design standard	EJMA
Working pressure	PN16 (Optional / Opsiyonel; PN25, PN40)
Working temperature	-80/+427°C (Optional / Opsiyonel; -80/+1100°C)
Nominal diameter	DN15 (1/2") - DN200 (8")
Connection material	ST37.2 Carbon Steel - Karbon Çelik (Optional / Opsiyonel; AISI 304/316)

DIMENSION TABLE

Size / Ölçü	Ød	A	± 50mm. B	± 100mm. A	B	kg
DN15	21,3	384	172	483	222	
DN20	26,9	438	197	553	254	
DN25	33,7	467	219	584	277	
DN32	42,4	511	237	641	303	
DN40	60,3	559	256	695	325	
DN50	76,1	645	289	794	364	3,67
DN65	88,9	778	348	953	429	
DN80	48,3	845	372	1029	464	
DN100	114,3	991	426	1191	526	
DN125	139,7	1130	477	1346	585	
DN150	168,3	1280	535	1511	650	
DN200	219,1	1527	620	1769	741	

MATERIAL LIST

No	Part	Qty	Material
1	Elbow 90° / 90° dirsek	2	St 37,2
2	Hose / Hortum	2	AISI 304/321

No	Part	Qty	Material
3	Braid / Örgü	2	AISI 304/321
4	Elbow 90° / °90 Dirsek	1	St 37,2
5	Fixing part / Sabitleme parçası	1	St 37,2
6	Drain plug / Tahliye Tapası	1	St 37,2
7	Band / Bant	4	AISI 304/321

PENDING REVIEW

At least one data plate field of this product could not be read from the source catalog and was left blank. Blank fields have not been estimated. Please confirm the values with the company before a binding offer.

DATA SOURCE

Metroend-Kompansator-Katalogu.pdf · printed page 64 (PDF 64)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

**METROEND MÜHENDİSLİK SAN. TİC.
LTD. ŞTİ**

Küçükbakkalköy Mah. Selvili Sk. No: 4, İç
Kapı No: 20, Ataşehir / İstanbul
+90 546 224 41 94 ·
sales@metroend.com

<https://vana.bogahost.com/en/expansion-joints/omega-flexes/omega-v-flex-butt-weld-mte-2030>
www.metroend.com