

OMEGA FLEXES

OMEGA V-FLEX GROOVED

MTE-2050



TECHNICAL DATA

Connection	Grooved - Yivli
Design standard	EJMA
Working pressure	PN16 (Optional / Opsiyonel; PN25, PN40)
Working temperature	-80/+427°C (Optional / Opsiyonel; -80/+1100°C)
Nominal diameter	DN50 (2") - DN200 (8")
Connection material	ST37.2 Carbon Steel - Karbon Çelik (Optional / Opsiyonel; AISI 304/316)

DIMENSION TABLE

Size / Ölçü	Ød	m	t	s	± 50mm. A	B	± 100mm. A	B
DN50	60,3	15,88	7,95	1,6	797	289	946	364
DN65	76,1	15,88	7,95	1,98	930	348	1105	429
DN80	88,9	15,88	7,95	1,98	997	372	1181	464
DN100	114,3	15,88	9,53	2,11	1143	426	1343	526
DN125	139,7	15,88	9,53	2,11	1282	477	1498	585
DN150	168,3	15,88	9,53	2,16	1432	535	1663	650
DN200	219,1	19,05	11,13	2,34	1730	620	1972	741

MATERIAL LIST

No	Part	Qty	Material
1	Elbow 90° / 90° dirsek	2	St 37,2
2	Hose / Hortum	2	AISI 304/321
3	Braid / Örgü	2	AISI 304/321
4	Elbow 90° / 90° Dirsek	1	St 37,2
5	Fixing part / Sabitleme parçası	1	St 37,2
6	Drain plug / Tahliye Tapası	1	St 37,2
7	Band / Bant	4	AISI 304/321

No	Part	Qty	Material
8	Grooved ends / Yivli boru	2	St 37,2

PENDING REVIEW

At least one data plate field of this product could not be read from the source catalog and was left blank. Blank fields have not been estimated. Please confirm the values with the company before a binding offer.

DATA SOURCE

Metroend-Kompansator-Katalogu.pdf · printed page 66 (PDF 66)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

METROEND MÜHENDİSLİK SAN. TİC. LTD.

ŞTİ

Küçükbakkalköy Mah. Selvili Sk. No: 4, İç

Kapı No: 20, Ataşehir / İstanbul

+90 546 224 41 94 ·

sales@metroend.com

<https://vana.bogahost.com/en/expansion-joints/omega-flexes/omega-v-flex-grooved-mte-2050>

www.metroend.com