

GATE VALVES

Resilient Seated Gate Valve



TECHNICAL DATA

Connection	DIN1092-2
Working pressure	PN16
Working temperature	-10°C / +120°C

WHERE IT IS USED

- Chemical - Petrochemical
- Water - Wastewater
- Heating - Cooling Systems
- Maritime Applications
- Mining Applications
- Power Stations

DIMENSION TABLE

DN DN	ØD	Øk	PN10 Øg	b	Ødxn	ØD	Øk	PN16 Øg	b	Ødxn	H H	L L	ØR	KG KG
40	150	110	84	18	19x4	150	110	84	18	19x4	185	140	200	10
50	165	125	99	20	19x4	165	125	99	20	19x4	190	150	200	11
65	185	145	118	20	19x4	185	145	118	20	19x4	210	170	200	15
80	200	160	132	22	19x8	200	160	132	22	19x8	235	180	254	16
100	220	180	156	24	19x8	220	180	156	24	19x8	265	190	254	22
125	250	210	184	26	19x8	250	210	184	26	19x8	350	200	315	38
150	285	240	211	26	23x8	285	240	211	26	23x8	380	210	315	45
200	340	295	266	26	23x8	340	295	266	26	23x12	490	230	315	78
250	395	350	319	28	23x12	405	355	320	32	28x12	615	250	406	120
300	445	400	370	28	23x12	460	410	370	32	28x12	700	270	406	165

MATERIAL LIST

No	Part	Material
1	BODY	GG25 / GGG40

No	Part	Material
2	DISC	EPDM + GGG40
3	WEDGE	GG25 / GGG40
4	STEM	AISI420
5	GASKET	EPDM / NBR
6	BONNET	GG25 / GGG40
7	HANDWHEEL	GG25

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 40 (PDF 43)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

METROEND MÜHENDİSLİK SAN. TİC. LTD. ŞTİ

Küçükbakkalköy Mah. Selvili Sk. No: 4, İç Kapı No:
20, Ataşehir / İstanbul

+90 546 224 41 94 · sales@metroend.com

<https://vana.bogahost.com/en/products/valves/gate-valves/resilient-seated-gate-valve>

www.metroend.com