

SOUNDING COCK VALVES

Sounding Cock Valve



TECHNICAL DATA

Connection	DIN2999
Working pressure	PN2,5
Working temperature	-10°C / +120°C

WHERE IT IS USED

- Maritime Applications
- Water - Wastewater

DIMENSION TABLE

DN	R	L	L1	H	KG
40	1 1/2"	130	180	60	3
50	2"	140	180	60	3

MATERIAL LIST

No	Part	Material
1	BODY	RG5
2	CYLINDER	RG5
3	O-RING	NBR
4	BONNET	RG5
5	LEVER	GGG40
6	NOZZLE	BRASS
7	GASKET	NBR

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 92 (PDF 95)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

**METROEND MÜHENDİSLİK SAN.
TİC. LTD. ŞTİ**

Küçükbakkalköy Mah. Selvili Sk. No:
4, İç Kapı No: 20, Ataşehir /
İstanbul
+90 546 224 41 94 ·
sales@metroend.com

<https://vana.bogahost.com/en/products/marine-equipment/sounding-cock-valves/sounding-cock-valve>
www.metroend.com