

GATE VALVES

Stainless Steel Threaded Gate Valve



TECHNICAL DATA

Connection	DIN2999
Working pressure	PN16
Working temperature	-20°C / +150°C

WHERE IT IS USED

- Chemical - Petrochemical
- Water - Wastewater
- Heating - Cooling Systems
- Maritime Applications
- Mining Applications
- Power Stations

DIMENSION TABLE

DN	NPS	L	E	H	KG
15	1/2"	54	54	95	0,26
20	3/4"	60	64	105	0,36
25	1"	63	71	115	0,55
32	1 1/4"	71	77	130	0,78
40	1 1/2"	78	96	145	1,05
50	2"	88	96	160	1,65

MATERIAL LIST

No	Part	Material
1	BODY	AISI304 /
2	BONNET	AISI304 /
3	WEDGE	AISI304 /
4	GASKET	PTFE
5	STEM	AISI304 /

No	Part	Material
6	O-RING	PTFE
7	HANDWHEEL	HT200
8	SCREW	AISI304 /

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 44 (PDF 47)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

**METROEND MÜHENDİSLİK SAN. TİC.
LTD. ŞTİ**

Küçükbakkalköy Mah. Selvili Sk. No: 4,
İç Kapı No: 20, Ataşehir / İstanbul
+90 546 224 41 94 ·
sales@metroend.com

<https://vana.bogahost.com/en/products/valves/gate-valves/stainless-steel-threaded-gate-valve>
www.metroend.com