

NEEDLE VALVES

Stainless Steel Threaded Needle Valve



TECHNICAL DATA

Connection	DIN 2999
Working pressure	6000 PSI
Working temperature	-40°C / +250°C

WHERE IT IS USED

- Power Plants
- Chemical - Petrochemical
- Maritime Applications
- Heating - Cooling Systems
- Food
- Mining Applications

MATERIAL LIST

No	Part	Material
1	BODY	AISI316
2	DOWEL	AISI316
3	PACKING	PTFE
4	BONNET	AISI316
5	UPPER STEM	AISI316
6	SET SCREW	AISI316
7	HANDLE	ALUMINIUM
8	PACKING WASHER	AISI316

PENDING REVIEW

At least one data plate field of this product could not be read from the source catalog and was left blank. Blank fields have not been estimated. Please confirm the values with the company before a binding offer.

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

**METROEND MÜHENDİSLİK SAN.
TİC. LTD. ŞTİ**

Küçükbakkalköy Mah. Selvili Sk.
No: 4, İç Kapı No: 20, Ataşehir /
İstanbul
+90 546 224 41 94 ·
sales@metroend.com

<https://vana.bogahost.com/en/products/valves/needle-valves/stainless-steel-threaded-needle-valve>
www.metroend.com