

SOLENOID VALVES

Stainless Steel Threaded Solenoid Valve



TECHNICAL DATA

Connection	DIN 2999
Working pressure	PN16
Working temperature	-10°C / +160°C

WHERE IT IS USED

- Power Plants
- Chemical - Petrochemical
- Maritime Applications
- Heating - Cooling Systems
- Food
- Mining Applications
- Water - Wastewater

DIMENSION TABLE

DN	NPS	A	B	H	KG
10	3/8"	66	48	107	0,75
15	1/2"	65	48	107	0,75
20	3/4"	75	58	112	0,90
25	1"	96	70	131	1,30
32	1 1/4"	131	96	146	2,60
40	1 1/2"	131	96	146	2,60
50	2"	165	120	167	4,40

MATERIAL LIST

No	Part	Material
1	BODY	AISI304 / AISI316
2	PLUNGER SEAL	VITON
3	ENCLOSING TUBE	AISI430 / AISI304

No	Part	Material
4	PLUNGER	AISI430
5	SPRING	AISI302
6	SHADING RING	COPPER
7	SEAT	ST.STEEL
8	O-RING	VITON
9	DIAPHRAM SEAT	SEAL VITON
10	COVER SCREWS	ST.STEEL
11	COVER	AISI304 / AISI316

PENDING REVIEW

At least one data plate field of this product could not be read from the source catalog and was left blank. Blank fields have not been estimated. Please confirm the values with the company before a binding offer.

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 80 (PDF 83)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

METROEND MÜHENDİSLİK
SAN. TİC. LTD. ŞTİ

Küçükbakkalköy Mah. Selvili
Sk. No: 4, İç Kapı No: 20,
Ataşehir / İstanbul
+90 546 224 41 94 ·
sales@metroend.com

<https://vana.bogahost.com/en/products/valves/solenoid-valves/stainless-steel-threaded-solenoid-valve>
www.metroend.com