

CHECK VALVES

Stainless Steel Threaded Spring Loaded Vertical Check Valve



TECHNICAL DATA

Connection	DIN2999
Working pressure	PN16
Working temperature	-10°C / +200°C

WHERE IT IS USED

▪ Chemical - Petrochemical	▪ Maritime Applications
▪ Water - Wastewater	▪ Mining Applications
▪ Heating - Cooling Systems	▪ Power Stations

DIMENSION TABLE

DIN2999	kolon_2	kolon_3	PN16	kolon_5
1	GÖVDE	BODY		AISI304 / AISI316
2	DİSK	DISC		AISI304 / AISI316
3	YAY	SPRING		AISI304 / AISI316
4	KAPAK	BONNET		AISI304 / AISI316
5	CONTA	GASKET	PTFE	

MATERIAL LIST

No	Part	Material
1	BODY	AISI304 / AISI316
2	DISC	AISI304 / AISI316
3	SPRING	AISI304 / AISI316
4	BONNET	AISI304 / AISI316
5	GASKET	PTFE

PENDING REVIEW

At least one data plate field of this product could not be read from the source catalog and was left blank. Blank fields have not been estimated. Please confirm the values with the company before a binding offer.

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 67 (PDF 70)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

METROEND
MÜHENDİSLİK SAN.
TİC. LTD. ŞTİ

Küçükbakkalköy Mah.
Selvili Sk. No: 4, İç
Kapı No: 20, Ataşehir
/ İstanbul
+90 546 224 41
94 ·
sales@metroend.com

<https://vana.bogahost.com/en/products/valves/check-valves/stainless-steel-threaded-spring-loaded-vertical-check-valve>
www.metroend.com