

CHECK VALVES

Stainless Steel Threaded Swing Check Valve



TECHNICAL DATA

Connection	DIN2999
Working pressure	PN16
Working temperature	-25°C / +210°C

WHERE IT IS USED

- Chemical - Petrochemical
- Water - Wastewater
- Heating - Cooling Systems
- Maritime Applications
- Mining Applications
- Power Stations

DIMENSION TABLE

kolon_1	DIN2999	kolon_3	kolon_4	kolon_5	kolon_6	PN16
1	TAPA		PLUG			AISI304 / AISI316
2		TAPA CONTASI		PLUG GASKET	PTFE	
3	GÖVDE		BODY			AISI304 / AISI316
4	CIVATA		BOLT			AISI304 / AISI316
5		KLAPE CONTASI		DISC GASKET	PTFE	
6	MİL		PIN			AISI304 / AISI316
7	KLAPE		DISC			AISI304 / AISI316

MATERIAL LIST

No	Part	Material
1	PLUG	AISI304 / AISI316
2	PLUG GASKET	PTFE
3	BODY	AISI304 / AISI316
4	BOLT	AISI304 / AISI316
5	DISC GASKET	PTFE

No	Part	Material
6	PIN	AISI304 / AISI316
7	DISC	AISI304 / AISI316

PENDING REVIEW

At least one data plate field of this product could not be read from the source catalog and was left blank. Blank fields have not been estimated. Please confirm the values with the company before a binding offer.

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 69 (PDF 72)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

**METROEND MÜHENDİSLİK
SAN. TİC. LTD. ŞTİ**

Küçükbakkalköy Mah. Selvili
Sk. No: 4, İç Kapı No: 20,
Ataşehir / İstanbul
+90 546 224 41 94 ·
sales@metroend.com

<https://vana.bogahost.com/en/products/valves/check-valves/stainless-steel-threaded-swing-check-valve>
www.metroend.com