

FIRE HOSE VALVES

Threaded Fire Hose Valve



TECHNICAL DATA

Connection	DIN 2999
Working pressure	PN16
Working temperature	-10°C / +80°C

WHERE IT IS USED

- Used in fire lines.

DIMENSION TABLE

DN	NPS	H	kolon_4	KG
40	1 1/2"	161	80	1,60
50	2"	177	100	2,00
65	2 1/2"	211	100	3,90

MATERIAL LIST

No	Part	Material
1	BODY	BRASS
2	DISC GASKET	NBR
3	DISC	BRASS
4	BONNET	BRASS
5	GASKET	NBR
6	STEM	BRASS
7	HANDWHEEL	GG25

PENDING REVIEW

At least one data plate field of this product could not be read from the source catalog and was left blank. Blank fields have not been estimated. Please confirm the values with the company before a binding offer.

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 102 (PDF 106)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

METROEND MÜHENDİSLİK SAN. TİC. LTD. ŞTİ

Küçükbakkalköy Mah. Selvili Sk. No: 4, İç Kapı

No: 20, Ataşehir / İstanbul

+90 546 224 41 94 · sales@metroend.com

<https://vana.bogahost.com/en/products/valves/fire-hose-valves/threaded-fire-hose-valve>

www.metroend.com