

SIGHT GLASSES

Threaded Sight Glass



TECHNICAL DATA

Connection	DIN 2999
Working pressure	PN16
Working temperature	-10°C / +80°C

WHERE IT IS USED

- Power Plants
- Chemical - Petrochemical
- Maritime Applications
- Heating - Cooling Systems
- Food
- Mining Applications
- Water - Wastewater

DIMENSION TABLE

DN	R	L	h	KG
15	1/2"	100	15	1,40
20	3/4"	125	15	1,50
25	1"	135	20	2,00
32	1 1/4"	160	20	3,10
40	1 1/2"	185	20	4,00
50	2"	200	25	6,00

MATERIAL LIST

No	Part	Material
1	BODY	GG25 / AISI304 / AISI316
2	COVER	GG25 / AISI304 / AISI316
3	GLASS	SEKURITE
4	BODY SEAL	PTFE

No	Part	Material
5	BOLT	5.6.

DATA SOURCE

Metroend-Urun-Katalogu.pdf · printed page 83 (PDF 86)

All content in this datasheet is taken from the catalog page referenced above; values are transferred verbatim, with no estimation or unit conversion. It contains no price or stock information.

**METROEND MÜHENDİSLİK SAN. TİC.
LTD. ŞTİ**

Küçükbakkalköy Mah. Selvili Sk. No: 4, İç
Kapı No: 20, Ataşehir / İstanbul
+90 546 224 41 94 ·
sales@metroend.com

<https://vana.bogahost.com/en/products/process-equipment/sight-glasses/threaded-sight-glass>
www.metroend.com